

DECLARATION OF PERFORMANCE NO: 0308/14783/2008

1. Unique identification code of the product-type: RHEINZINK-flat lock-tile
005031081000000000
2. Intended use: Fully supported roof coverings, external cladding of walls, facades or internal lining.
3. Manufacturer: RHEINZINK GmbH & Co. KG
Bahnhofstraße 90
45711 Datteln
Germany
4. System of AVCP: 4
5. Harmonised standard: EN 14783:2013
Notified body: ./.. Not applicable by system of assessment and verification of constancy of performance no. 4


6. Declared performances:

Essential characteristics	Performance
Water permeability	Impermeable
Vapour diffusion- and air tightness	Water vapour impermeable
Reaction to fire (EN 13501-1)	A1 (without testing, 96/603/EG)
Dimensional change	$22 \cdot 10^{-6} \text{K}^{-1}$
Durability	Titanium zinc according to EN 501 + EN 988, RHEINZINK-CLASSIC, RHEINZINK-prePATINA & RHEINZINK-GRANUM: patina forming material The following coatings are available: Top side: transparent polyester-coating Button side: papyrus white polyester-coating RHEINZINK-artCOLOR: Top side: PVDF-color-coating Button side: papyrus white polyester-coating
External fire performance (only for roof coverings, EN 13501-5)	Definitions fulfilled according to 2000/553/EG,

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Datteln, 01.01.2020



Bettina Wellner
Head of Quality Control



Steven Paton
Head of department
Product and Innovation Management